

## INTRODUCTION

A revolutionary step change in low-level access. The Ecolift Tower is easy, fast, efficient to use, it's intuitive and hassle free compared to traditional podiums and scaffold towers. Simply step in and turn the handle and up you go! And you don't need power; no batteries to charge or mains power consumption.

With the introduction of our range of non-powered, powered access machines, gone are the days of assembling climbing steps, access towers and podiums, no more slips, trips or having to balance.

- Step into the platform, no climbing.
- Intuitive to operate – turn the handle to elevate. Patented lift mechanism, no power required.
- 'Auto-lok' brake on elevation.
- Lightweight, easy to manoeuvre.
- Small footprint
- Unlimited lift cycles, can be used 24/7.
- Robust design for years of trouble free service.
- Minimal operational costs, virtually maintenance free.



Working Dimensions	Standard	Wind Rated
Maximum Working Height	4.20 m	
Maximum Platform Height	2.20 m	
Basket Dimensions	850 mm (L) x 644 mm(W)	
Working Footprint	1.28 m x 700 m	1.28 m x 950 mm
Safe Working Load	150 kg (1 person + tools)	
Maximum Manual Force	200 N	
Maximum Gradient for Operation	0 degrees	3°
Maximum Wind Force	Internal use only, 0 (zero) mph	Internal/External use. 28mph
Maximum Wheel Force	234 kg	245 kg
Maximum Castor Point Load	234 kg (2.29 kN)	245 kg (2.4 kN)
Sound Pressure Level	Less than 70 dB(A)	

Closed Dimensions		
Length	1.28 m	1.28 m
Width	0.70 m	0.95 m
Height	1.94 m	1.94 m
Weight	305 kg	335 kg