

HM25LV breakers when used with the Beaver Powerpack give the ultimate in terms of performance and ultra low hand arm vibration levels.

Unique JCB patented active hydraulic suspension dispenses of traditional springs and bushes to give single axis vibration of 1.6m/s<sup>2</sup>.

## HM25LV

|                                       |                    |
|---------------------------------------|--------------------|
| Model name                            | HM25LV             |
| Model number                          | 929/A6000          |
| Weight kg (lb)                        | 27 (60)            |
| Tool / chisel size hex mm (in)        | 32 (1 1/4)         |
| Hydraulic flow l/min (gal/min)        | 18-22 (4-5)        |
| Pressure range Bar (psi)              | 90-110 (1305-1595) |
| Blow frequency blows/min              | 1500               |
| Vibration (BS8622-5) m/s <sup>2</sup> | 1.6                |
| Sound power level dB Lwa              | 108                |



Practical handle protection: replaceable rubber buffers protect the handles and give long service life

Immediate response trigger: gives the operator easier control and increased comfort



New ultra low vibration system: reduces hand arm vibration by 60% to 1.6m/s<sup>2</sup> (single axis)

Compact design: The HM25LV handles are more than 50mm lower than the HM25 breaker making it more compact and easier to use and transport

Powerful new power cell: gives increased blow energy which hits harder giving greater output