

SPECIFICATION SHEET



1061-MANHOLE RING CLAMPS



Torsionally rigid, light-weight hollow steel construction for the transportation and placement of manhole rings. The pipe tackle complies with official labour safety regulations and is equipped with a safety lock. Inadvertent slipping of the load through the claws is prevented by a spring on each clamp.

Advantages:

Clamping range adjustable by a special screw

Heavy-duty galvanized chains in accordance with DIN 5688.5

Product Code	SWL (kg)	CLAWS	Face Mat	Clamp Range (mm)	Depth	Chain Length (m)	Pipe Size	Weight (kg)
1061.1	1500	3	Ribbed	0-130	200	1.70	2m Max	31
1061.2	1500	3	Ribbed	0-130	200	2.30	3m Max	34
1061.3	1500	3	Rubber	0-75	200	1.70	2m Max	32
1061.4	3000	3	Ribbed	10-180	220	1.80	2m Max	54
1061.5	3000	3	Ribbed	10-180	220	2.50	3m Max	58
1061.6	3000	3	Rubber	10-135	220	1.80	2m Max	56
1061.7	4000	4	Ribbed	50-180	220	2.50	3m Max	83

Appearance may vary from picture above.

Eichinger Equipment Ltd
69-73 James Road, Frimley, Camberley, GU15 2RH
T: 01276 605 970 F: 01276 682 913 E: sales@eichinger.co.uk