

SPECIFICATION SHEET



1062-MANHOLE RING CLAMPS



Torsionally rigid light-weight sheet steel construction for the transportation and placement of upright pipes and cones. The shaft ring clamps have been designed in conformance with official labour safety regulations and are equipped with safety locks. (Pre-tensioned springs).

Due to a special automatic lifting device, the arduous task of lifting the clamps is eliminated. Designed for all standard shaft rings and cones. Shaft rings according to DIN4034, Part1, shaft rings according to DIN4034, Part2, thin-walled shaft rings, coated shaft rings. Taper and conical shaft rings and cones according to DIN4034.

Advantages:

- High-strength, galvanized chain according to DIN5688.5.
- Ribbed rubber max.2.0m.

Product Code	SWL (kg)	CLAWS	Face Mat	Clamp Range (mm)	Depth	Chain Length (m)	Pipe Size	Weight (kg)
1062.1	1500	3	Ribbed	40-140	310	1.70	2m Max	38
1062.2	1500	3	Ribbed	40-140	310	2.50	3m Max	40
1062.3	1500	3	Rubber	0-100	310	1.70	2m Max	38
1062.4	3000	3	Ribbed	60-160	310	1.70	2m Max	41
1062.5	3000	3	Ribbed	60-160	310	2.50	3m Max	43
1062.6	3000	3	Rubber	0-120	310	1.70	2m Max	58
1062.7	4000	4	Ribbed	60-160	310	1.70	2m Max	58
1062.8	5000	3	Ribbed	100-230	370	2.50	2m Max	140
1062.9	5000	3	Rubber	100-230	370	2.90	3m Max	150

Appearance may vary from picture above.

Eichinger Equipment Ltd

69-73 James Road, Frimley, Camberley, GU15 2RH

T: 01276 605 970 F: 01276 682 913 E: sales@eichinger.co.uk