



| Weight   |                      |
|--|----------------------|
| Unladen  | 5010 kg              |
| Shipping   | 4886 kg              |
| Capacities   |                      |
| Max. Safe Load   | 6000 kg              |
| Heaped   | 3150 litres          |
| Struck   | 2550 litres          |
| Water  | 1650 litres          |
| Engine   |                      |
| <ul style="list-style-type: none"> <li>● Deutz TCD 3.6 L4, water-cooled, 4-cylinder, charged air cooled turbo, fuel injected, diesel and after treatment Diesel Particulate filter</li> <li>● Power 55.4 kW / 74 bhp at 2200 rpm</li> <li>● Torque 405 Nm (299 lbf ft).</li> </ul> |                      |
| Noise Levels   |                      |
| Operator's Ear   | 84 LpA               |
| Airborne   | 101 LwA              |
| Transmission   |                      |
| Torque converter four speed forward and reverse Powershuttle transmission, column mounted speed and directional control lever  |                      |
| Speeds – Forward and Reverse   |                      |
| 1  | 5.0 km/h (3.1 mph)   |
| 2  | 8.0 km/h (5.0 mph)   |
| 3  | 15.1 km/h (9.3 mph)  |
| 4  | 27.7 km/h (17.3 mph) |
| Brakes and Axles   |                      |
| <ul style="list-style-type: none"> <li>● Totally enclosed multiplate oil-immersed discs mounted on rear axle &amp; auto wear adjustment</li> <li>● Hand operated parking brake (SAHR)</li> </ul>   |                      |

| Kinglink Chassis  |           |
|---|-----------|
| Constructed from folded steel plate, with three point Kinglink giving articulation and oscillation for better stability, traction and safety on site.   |           |
| Skip  |           |
| <ul style="list-style-type: none"> <li>● Hydraulically operated, 8mm steel base plate</li> <li>● Skip mouth &amp; sides reinforced with box sections</li> <li>● Power Swivel Skip enables a 180° rotation.</li> </ul>         |           |
| Seating & Controls  |           |
| <ul style="list-style-type: none"> <li>● Adjustable suspension seat with high-vis seat belt</li> <li>● Clear operators display unit contains all warning lamps</li> </ul>   |           |
| Service Access  |           |
| <ul style="list-style-type: none"> <li>● Lockable engine cover provides access to the engine</li> <li>● Keyless lockable side covers for ground level service points</li> </ul>   |           |
| Electrics   |           |
| <ul style="list-style-type: none"> <li>● Fuse &amp; relay are housed on a central power distribution board.</li> <li>● Main harness is fully enclosed in solid conduit and incorporates the engine diagnostic port</li> </ul> |           |
| Steering & Hydraulics   |           |
| <ul style="list-style-type: none"> <li>● Hydraulic power steering</li> <li>● Return line filtration for all services</li> <li>● Hydraulic test point fitted as standard</li> </ul>  |           |
| Tank Capacities   |           |
| Fuel  | 72 Litres |
| Hydraulic   | 50 Litres |
| Turning Circle  |           |
| 16.6m   |           |

**Standard Equipment**

- Full LED road lighting incl. DRL (daylight running lights)
- Camera and dashpanel monitor
- LED beacons
- Fan guard
- Reverse alarm
- Air conditioning

**Optional Equipment**

- Adjustable work lights
- Air suspension seat
- Rear wiper system
- Wheel nut indicator
- GPS speedometer
- USB socket