



UTILITIES



HIGHWAYS



CONSTRUCTION



AIRPORTS

NEW

680 mm JIB

JCB Attachments are pleased to announce the launch of the new lifting equipment 680 mm JIB compatible with JCB machines.

- Designed to ensure ease of use and greater control when placing loads
- The 680 mm JIB enables the operator to place a load using crowd and dump
- This attachment is the best choice when you require to place suspended loads close to buildings as the hook is at the very end of the JIB
- This attachment is available for all Q-fit JCB Loadall models*
- This is the only approved 680 mm JIB for JCB machines and testing has been completed to ensure it complies with current lifting legislations
- 680 mm is the distance between the pick-up and the hook
- Capable of lifting loads up to 4T**

* Providing it is within the machine capacity

** Please refer to the lifting and stability charts in your machine to determine maximum lifting weight for the height you are working at

Learn more at: jcb.com



#completingthesolution

PART NUMBER	STRUCK CAPACITY M ³	HEAPED CAPACITY M ³	PIN CTRS MM	PIN DIAMETER MM	MASS KG	WIDTH (W) IN.	HEIGHT (H) MM	DEPTH (D) MM	METAL THICKNESS MM	MACHINE FITMENT
980/A0425	0.19	0.23	385	65	335	18	1170	1391	20	JS130 / JS115 - JS145 / 131X - 150X
980/A0426	0.25	0.3	385	65	371	24	1170	1391	20	JS130 / JS115 - JS145 / 131X - 150X
980/B0951	0.31	0.35	450	80	618	24	1338	1588	25	JS200 - JZ255 / 210X-220X

Completing the solution: Using a JCB Attachment with a JCB machine provides the ultimate complete package. Please contact JCB Attachments if you have any questions or visit <https://www.jcb.com/en-gb/attachments>