

## Hinowa Swivel Minidumper TX3005 SPECIFICATION SHEET



Combining maximum comfort and performance, our Minidumpers are an innovative, modern tracked machine designed to fit the requirements of a wide range of industries including landscaping, construction work, farm transportation, tunnel work and restoration. Our Minidumpers are the ideal hire solution for working on uneven, muddy, sandy or sloping ground where wheels are unsuitable due to lost grip or sinking risk.

## Technical Data

Diesel Engine	
Brand	Kubota V 2403
Emission regulation	Stage V
Pistons and displacement	n °4 da 2 197 cc
Max gross power	50HP – 37.4 kW @ 2700 rpm
Starting	Electric
Fuel tank	45 litres
Granted noise level	Lwa 101 dB
Distributor	
Type	Mechanical
Hydraulic Pumps	
Number and type	n°2 piston pumps + n°1 gear pump
Tracks	
Track tensioner	Grease
Track width	320 mm
Rollers per side	2 fixes and 4 floating
Fixed undercarriage	1550 mm
Performance	
Translation speed	6 – 11 km/h
Max. inclination	20° (36.4%)
Capacity	2875 kg
Dumper Bed Capacity	
Rated volume (ISO 6483)	1.49 m <sup>3</sup>
Struck volume	1.09 m <sup>3</sup>
Dumper Bed Capacity	
Operating weight (without operator)	2750 kg

